



P. C. B. LAYOUT

**SPECIFICATION:**

Current Rating: 1.5AMP  
 Contact Resistance: 20m Ω (max)  
 Insulation Resistance: 1000M Ω Min at 500V DC  
 Dielectric Strength: 500V AC Per 1 Minute  
 Operating Temperature: -40°C TO +105°C

**MATERIALS:**

Insulator: PA6T+30% Glass Fiber, UL94V-0  
 Contact: Brass  
 Contact plated: Gold Over Nickel

Poles	Part No.	Dimension mm		
		A	B	C
6	B-3002R06P-0110	13.34	12.24	4.00
8	B-3002R08P-0110	15.34	14.24	6.00
10	B-3002R10P-0110	17.34	16.24	8.00
12	B-3002R12P-0110	19.34	18.24	10.00
14	B-3002R14P-0110	21.34	20.24	12.00
16	B-3002R16P-0110	23.34	22.24	14.00
18	B-3002R18P-0110	25.34	24.24	16.00
20	B-3002R20P-0110	27.34	26.24	18.00
24	B-3002R24P-0110	31.34	30.24	22.00
26	B-3002R26P-0110	33.34	32.24	24.00
28	B-3002R28P-0110	35.34	34.24	26.00
30	B-3002R30P-0110	37.34	36.24	28.00
34	B-3002R34P-0110	41.34	40.24	32.00
40	B-3002R40P-0110	47.34	46.24	38.00
44	B-3002R44P-0110	51.34	50.24	42.00
50	B-3002R50P-0110	57.34	56.24	48.00
60	B-3002R60P-0110	67.34	66.24	58.00
64	B-3002R64P-0110	59.34	58.24	50.00

APPROVED:	DATE:	Ckmtw 深圳市灿科盟实业有限公司 CHANKLEMENT INDUSTRYCO., LTD			
CHECKED:	DATE:	TITLE: 300-2R-XP (2.0弯筒牛)			
DRAWN: LYF	DATE: 2024-04-10	Part NO.	B-3002RXXP-0110		
		UNIT	mm	SCALE	free
		FILE NO.	Ckmtw-300-0004	REV.	A

TOLERANCE TABLE	
.0	±0.20
.00	±0.10
.000	±0.05